

Certificate of quality

Metalubs X CL - engine cleaner

Domain: High-tech cleaner for petrol, diesel and gas operated engines, switch-gears and differential gears.

Dosage:

Pour the contents of Metalubs X CL (250 ml) to the used oil before oil change, then run the engine for 10 to 15 minutes. The contents of one bottle is sufficient for cleaning an engine between 5 to 8 liters of oil capacity. After cleaning is done the oil filter must be replaced.

Appearance

Physical State:	liquid
Color:	brownish
Odor:	characteristic

Safety-related data

Flashpoint:	65°C	Hazard class A III
Boiling point/boiling range:	170-195°C	
Vapor pressure at 20°C:	< 0.1mbar	
Density at 20°C:	0,87 g/cm ³	
Ignition temperature:	cca. 220°C	(for oil distillate)
Water solubility:	insoluble at 20°C	
pH-value:	7 to 9	
Kinematic viscosity at 40°C:	12 mm ² /s	
Flammability (solid, gaseous):	Not flammable	
Oxidizing properties:	Not oxidizing	
Auto-ignition temperature:	Not self-igniting	
Solubility in other solvents:	Well soluble in most oils	

The products are made in Germany for Metalubs LTD, who is responsible and offers warranty for the distributed products.

