

Certificate of quality

Metalubs X Old- Anti-wear eco product

Domain: It is recommended for all worn combustion engines with high oil consumption - whether they are petrol, diesel, Wankel, gas or turbo.

Dosage:

Replace 5 to 10% by volume engine oil and 10% of gear oil with X Old. Fill in X Old into the warm engine. Heat the bottle to 25-30 degrees, turn it upside down and shake well before use. Let the engine run for a short time or drive on. Not a single treatment product, use it at the same ration in case of each oil change.

Appearance

Physical State:	liquid
Color:	yellowish
Odor:	characteristic

Safety-related data

Flashpoint:	285°C
Ignition temperature:	430°C
Vapor pressure at 20°C:	< 0.13 mbar
Density at 20°C:	1.05 g/cm ³
Bulk density:	not applicable
Water solubility:	insoluble at 20°C
pH-value:	7 to 9
Kinematic viscosity at 40°C:	350 mm ² /s
Flammability (solid, gaseous):	Not flammable
Oxidizing properties:	Not oxidizing
Auto-ignition temperature:	Not self-igniting
Melting point/melting range:	< -5°C
Solubility in other solvents:	Well soluble in most oils

The products are made in Germany for Metalubs LTD, who is responsible and offers warranty for the distributed products.

